

## 1 Introduction

This document details the thermal performance calculation of the window configuration as detailed below.

The frame profile results detailed below are provided by computer simulation using LBL software program THERM 5.2 and validated against proofs in Annex D (D1 to D10) of BS EN ISO 10077-2:2012. The frame profile results detailed below are provided from methods contained in BS EN ISO 10077-1:2006 and in accordance with thermal transmittance requirements detailed in BS EN 14351-1:2006+A1:2010.

## 2 Summary of Results

### 2.1 Frame thermal transmittance (in accordance with BS EN ISO 10077-1:2006)

Frame Profile	Frame Thermal Transmittance ( $U_f$ )
Casement	1.4 W/m <sup>2</sup> K

### 2.2 Linear thermal transmittance (in accordance with BS EN ISO 10077-2:2012)

Frame Profile	Linear Thermal Transmittance ( $\psi$ )
Casement	0.038 W/m.K

### 2.3 Centre pane U-Value of glazing calculated in accordance with BS EN 673: 2011

Glazing unit	Centre pane U-value ( $U_g$ )
Nominal dimensions 4-16-4 90% argon 10% air filled, normal emissivity 0.03 (4mm low-e float outer pane, 4mm low-e inner pane and 16mm Thermobar spacer)	1.1 W/m <sup>2</sup> K

### 2.4 U-Value

The thermal performance of the window ( $U_w$ ) in accordance with EN ISO 10077-1:2006 is:

<b>1.3 W/m<sup>2</sup>K</b>
-----------------------------

All profile calculations based on BS EN ISO 10077-2:2012

*The legal validity of this report can only be claimed on presentation of the complete report.*